

Safety Data Sheet
 according to 1907/2008/EC (REACH), 1272/2008/EC (CLP), and
 GHS

Revision: 15.04.2014

Printing date 15.04.2014

1 Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: DURAC Plus Liquid Fill for Thermometers
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
No further relevant information available.
- Application of the substance / the mixture Product Component
- 1.3 Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier:
H-B Instrument – A Division of Bel-Art Products
102 West Seventh Avenue
Trappe, PA 19426 USA
Phone: (610) 489-5500
- 1.4 Emergency telephone number:
ChemToll Inc.
(800)255-3924, +1 (813)248-0585

2 Hazards identification

- 2.1 Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2

H225: Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.


STOT SE 3 H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi: Irritant

R36: Irritating to eyes.



F+ Highly flammable

R11: Highly flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Safety Data Sheet
 according to 1907/2008/EC (REACH), 1272/2008/EC (CLP), and
 GHS

Printing date 15.04.2014

Revision: 15.04.2014

Trade name: DURAC Plus Liquid Fill for Thermometers

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

(Contd. of page 1)

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280 Wear protective gloves / eye protection.

P261 Avoid breathing mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

Additional information: Repeated exposure may cause skin dryness or cracking.

Hazard description:

WHMIS-symbols:

B2 - Flammable liquid

D2B - Toxic material causing other toxic effects



NFPA ratings (scale 0 - 4)

Health = 2

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 3)

Safety Data Sheet
 according to 1907/2008/EC (REACH), 1272/2008/EC (CLP), and
 GHS

Printing date 15.04.2014

Revision: 15.04.2014

Trade name: DURAC Plus Liquid Fill for Thermometers

(Contd. of page 2)

- **HMS Long Term Health Hazard Substances**
None of the ingredients is listed.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/Information on Ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.
- **Dangerous components:**

CAS: 67-64-1	acetone	
EINECS: 200-662-2	Xn R36	F R11
Index number: 606-001-00-8	H36-67	
	Flam. Liq. 2, H225	
	Eye Irrit. 2, H319; STOT SE 3, H336	
- **Additional Information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **4.1 Description of first aid measures**
- **General Information:**
Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.
- **After Inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
Irritant to eyes.
Slight irritant effect on skin and mucous membranes.
- Dizziness
- Nausea
- Gastric or intestinal disorders when ingested.
- Coughing
- Acidosis
- Disorientation
- Unconsciousness

(Contd. on page 4)

Safety Data Sheet
 according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
 GHS

Printing date 15.04.2014

Revision: 15.04.2014

Trade name: DURAC Plus Liquid Fill for Thermometers

(Contd. of page 3)

- **Hazards** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
If necessary oxygen respiration treatment.
Medical supervision for at least 48 hours.

5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
For safety reasons unsuitable extinguishing agents: None.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional Information**
Eliminate all ignition sources if safe to do so.
Cool endangered receptacles with water spray.
Use large quantities of foam as it is partially destroyed by the product.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation.
Keep away from ignition sources.
Protect from heat.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust!).
Pick up mechanically.
Send for recovery or disposal in suitable receptacles.
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
Prevent formation of aerosols.

(Contd. on page 5)

Trade name: DURAC Plus Liquid Fill for Thermometers

(Contd. of page 4)

- Keep away from heat and direct sunlight.
- Rags, metal woods / cuttings / shavings and waste papers soaked with product must be placed in a sealed metal container rated for flammable waste.
- Avoid splashes or spray in enclosed areas.
- Information about fire - and explosion protection:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Fumes can combine with air to form an explosive mixture.
- When heated the product forms flammable fumes.
- Flammable gas-air mixtures may form in empty receptacles.
- 7.2 Conditions for safe storage, including any incompatibilities**
- Storage:**
- Requirements to be met by storerooms and receptacles:
- Store in a cool location.
- Provide ventilation for receptacles.
- Avoid storage near extreme heat, ignition sources or open flame.
- Information about storage in one common storage facility:**
- Store away from foodstuffs.
- Do not store together with oxidizing and acidic materials.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- 8.1 Control parameters**
- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone	
IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm
PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm
	Long-term value: (1188) NIC-475 mg/m ³ , (500) NIC-200 ppm
BEI	
EL (Canada)	Short-term value: 500 ppm
	Long-term value: 250 ppm
EV (Canada)	Short-term value: 750 ppm
	Long-term value: 500 ppm

- DNELs** No further relevant information available.
- PNECS** No further relevant information available.

(Contd. on page 6)


Trade name: DURAC Plus Liquid Fill for Thermometers

(Contd. of page 5)

- Ingredients with biological limit values:**

67-64-1 acetone	
BEI (USA) 50 mg/L	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

- Additional information:** The lists valid during the making were used as basis.
- 8.2 Exposure controls**
- Personal protective equipment:**
- General protective and hygienic measures:**
- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid close or long term contact with the skin.
- Avoid contact with the eyes.
- Respiratory protection:**
- Not required under normal conditions of use.
- Use suitable respiratory protective device in case of insufficient ventilation.
- Use suitable respiratory protective device when aerosol or mist is formed.
- For spils, respiratory protection may be advisable.
- Protection of hands:**



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.
- Material of gloves**
- Butyl rubber, BR
- Fluorocarbon rubber (Viton)
- The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material**
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Not suitable are gloves made of the following materials:**
- Nitrile rubber, NBR
- PVC gloves
- PVA gloves

(Contd. on page 7)

Safety Data Sheet
 according to 1907/2008/EC (REACH), 1272/2008/EC (CLP), and
 GHS

Revision: 15.04.2014

Printing date 15.04.2014

Trade name: DURAC Plus Liquid Fill for Thermometers

(Contd. of page 6)

- Eye protection:
 - Safety glasses
- Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment
No further relevant information available.
- Risk management measures
- See Section 7 for additional information.
No further relevant information available.

9 Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:
 - Form: Liquid
 - Colour: Blue
 - Odour: Acetone-like
 - Odour threshold: Not determined.
 - pH-value: Not determined.
- Change in condition
 - Melting point/Freezing range: Not Determined.
 - Boiling point/Boiling range: 131 °F / 55 °C
 - Flash point: -4 °F / -20 °C
- Flammability (solid, gaseous): Not applicable.
- Auto/Self-ignition temperature: Not determined.
- Decomposition temperature: Not determined.
- Self-igniting: Product is not self-igniting.
- Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Explosion limits:
 - Lower: 2.6 Vol %
 - Upper: 13 Vol %
- Vapour pressure: Not determined.
- Density at 20 °C: 0.8 g/cm³
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not determined.

(Contd. on page 6)

Safety Data Sheet
 according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
 GHS

Revision: 15.04.2014

Printing date 15.04.2014

Trade name: DURAC Plus Liquid Fill for Thermometers

(Contd. of page 7)

- Solubility in / Miscibility with water: Fully miscible.
- Partition coefficient (n-octanol/water): Not determined.
- Viscosity:
 - Dynamic: Not determined.
 - Kinematic: Not determined.
- 9.2 Other Information: No further relevant information available.

10 Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions
 - Flammable: Reacts violently with oxidizing agents.
 - Used empty containers may contain product/gases which form explosive mixtures with air.
 - Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
 - Reacts with acids.
 - Toxic fumes may be released if heated above the decomposition point.
- 10.4 Conditions to avoid
 - Keep ignition sources away - Do not smoke.
 - Store away from oxidizing agents.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity:
 - LD₅₀/CS₅₀ values relevant for classification:

Oral	LD50 5800 mg/kg (rat)
Dermal	LD50 20000 mg/kg (rabbit)
- Primary irritant effect:
 - on the skin: Slight irritant effect on skin and mucous membranes.
 - on the eye: Irritant effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information: The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Revision: 15.04.2014

Printing date 15.04.2014

Trade name: DURAC Plus Liquid Fill for Thermometers

(Contd. of page 8)

Irritant
 Irritation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.
 At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
 Acute effects (acute toxicity, irritation and corrosivity): Vapours have narcotic effect.
 Repeated dose toxicity: Repeated exposure may cause skin dryness or cracking.

12 Ecological Information

- 12.1 Toxicity: No further relevant information available.
- 12.2 Persistence and degradability: No further relevant information available.
- 12.3 Bioaccumulative potential: No further relevant information available.
- 12.4 Mobility in soil: No further relevant information available.
- Additional ecological information:
- General notes:
 Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- 12.5 Results of PBT and vPvB assessment
 · PBT: Not applicable.
 · vPvB: Not applicable.
- 12.6 Other adverse effects: No further relevant information available.

13 Disposal considerations

- 13.1 Waste treatment methods
 · Recommendation
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
 Can be reused after reprocessing.
 Contact waste processors for recycling information.
- Uncleaned packaging:
 · Recommendation: Disposal must be made according to official regulations.
 · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

- 14.1 UN-Number UN1090
- DOT, ADR, IMDG, IATA

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Revision: 15.04.2014

Printing date 15.04.2014

Trade name: DURAC Plus Liquid Fill for Thermometers

(Contd. of page 9)

14.2 UN proper shipping name
 Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 1 L (0.3 gal).

- DOT Acetone
- ADR 1090 ACETONE
- IMDG, IATA ACETONE
- 14.3 Transport hazard class(es)
- DOT

Class 3 Flammable liquids.
 Label

ADR 3 (F-) Flammable liquids.
 Label

Class 3
 Label
 IMDG, IATA

- Class 3 Flammable liquids.
- Label
- 14.4 Packing group II
- DOT, ADR, IMDG, IATA
- 14.5 Environmental hazards:
 Marine pollutant: No
 Warning: Flammable liquids.
- 14.6 Special precautions for user
 · Danger code (Kemler): F-E-S-D
 · EMS Number: 33
 · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable.
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable.
- Transport/Additional information:
 · ADR 1L
 · Limited quantities (LQ) 2
 · Transport category D/E
 · Tunnel restriction code

(Contd. on page 11)

Printing date 15.04.2014

Revision: 15.04.2014

Trade name: DURAC Plus Liquid Fill for Thermometers

UN "Model Regulator":

UN1090, ACETONE, 3, II

(Contd. of page 10)

15 Regulatory Information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - United States (USA)
 - SARA
 - Section 305 (extremely hazardous substances):
None of the ingredients is listed.
 - Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
 - TSCA (Toxic Substances Control Act):
All ingredients are listed.
 - Proposition 65 (California):
Chemicals known to cause cancer:
None of the ingredients is listed.
 - Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
 - None of the ingredients is listed.
 - Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
 - Chemicals known to cause developmental toxicity:
None of the ingredients is listed.
 - Carcinogenic Categories
 - EPA (Environmental Protection Agency)
 - 67-84-1 acetone II
 - IARC (International Agency for Research on Cancer)
 - None of the ingredients is listed.
 - TLV (Threshold Limit Value established by ACGIH)
 - 67-84-1 acetone A4
 - NIOSH-Ca (National Institute for Occupational Safety and Health)
 - None of the ingredients is listed.
 - Canada
 - Canadian Domestic Substances List (DSL)
 - All ingredients are listed.
 - Canadian Ingredient Disclosure list (limit 0.1%)
 - None of the ingredients is listed.
 - Canadian Ingredient Disclosure list (limit 1%)
 - 67-84-1 acetone

(Contd. on page 12)

Printing date 15.04.2014

Revision: 15.04.2014

Trade name: DURAC Plus Liquid Fill for Thermometers

(Contd. of page 11)

- Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57
 - None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H225 Highly flammable liquid and vapour.
 - H319 Causes serious eye irritation.
 - H338 May cause drowsiness or dizziness.
 - R11 Highly flammable.
 - R38 Irritating to eyes.
 - R67 Repeated exposure may cause skin dryness or cracking.
 - R67 Vapours may cause drowsiness and dizziness.
- Abbreviations and acronyms:
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 - ACGIH: American Conference of Governmental Industrial Hygienists
 - ENCS: European Inventory of Existing Commercial Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - WHMIS: Workplace Hazardous Materials Information System (Canada)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - LD01: Lethal dose, 1 percent
 - LD02: Lethal dose, 2 percent
 - LD05: Lethal dose, 5 percent
 - LD10: Lethal dose, 10 percent
 - LD25: Lethal dose, 25 percent
 - LD50: Lethal dose, 50 percent
 - LD100: Lethal dose, 100 percent
 - STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- Sources
 - SDS Prepared by:
 - Chemtel Inc.
 - 1305 North Florida Avenue
 - Tampa, Florida USA 33602-2902
 - Toll Free North America 1-888-255-3924 Int. +01 813-248-0573
 - Website: www.chemtelinc.com